

GLOSS METER GMS/GM60

Standard package -

Gloss Meter GM Series

GM Gloss meter main unit	1
Standard board	1
USB cable	1
Data software	1
Power adapter	1
Operation manual	1
Carrying case	1

Optional accessories

SD card
Bluetooth module

GM Series gloss meters are designed and manufactured according to international standards ISO2813, ISO7668, ASTM D523, ASTM D2457 and China standards GB/T9754, GB/T13891, GB/T7706 and GB/T8807. The technical parameters is up to JJG696-2002. GM Series gloss meters can be widely used to measure painting, coating, plastic, ceramics, leather products, paper, printing, floor materials and so on. ●



KEY FEATURES

- ✦ Precision appearance design, more suitable for human characteristic, easy to use.
- ✦ Three-angle gloss data is displayed simultaneously, can satisfy various requirements. (Only for GMS)
- ✦ Large memory for measurement data.
- ✦ Latest Bluetooth function and removable memory card to transmit data conveniently.
- ✦ Special designed gloss software to analysis data and output.
- ✦ Prompt for low battery and full memory.

With internal Bluetooth module (only available for GMS) or USB interface, GM gloss meter can transfer data with PC easily. The measuring data also can be exported to printer via printing interface. Optional SD card makes the memory as large as you want.



Specifications

Model	GMS	GM60
Application	Painting, printing, floor material, plastic, ceramics, leather, hardware, plating	
Measuring Range(Gu)	0~120, 120~2000 @ 20° 0~120, 120~1000 @ 60° 0~120, 120~160 @ 85°	0~120, 120~1000 @ 60°
Readout Error(Gu)	±1.5 (0~120) ±1.5%(120~2000)	±1.5 (0~120) ±1.5%(120~1000)
Repeatability	±0.5 (0~120) ±0.5%(120~2000)	±0.5 (0~120) ±0.5%(120~1000)
Aperture (mm)	20°, 60°, 85°	60°
Measurement Spot (mm)	10×10 @ 20° 9×15 @ 60° 5×38 @ 85°	9×15
Memory	900 data or 30 groups, CF card (optional)	
Interface	USB / printer /Bluetooth (Bluetooth is only available for GMS)	
Software	Data managing software	
Power Supply	+5V, AA*4	
Working Environment	10~40°C, <85%RH,	
Dimension (mm)	164×58×88	
Net Weight(g)	520	
Standards	ISO2813, ISO7668, ASTM D523, ASTM D2457, GB/T9754, GB/T13891, GB/T7706, GB/T8807	



Standard package
-- GMS/GM60